PawSpa®
Powered by oxygenics®

SHOWER QUICK START GUIDE

STEP 1
Remove your existing shower head. To remove, turn the existing shower head in a counterclockwise direction.





STEP 2
Attach end of hose to shower arm and hand tighten.

STEP 3
Attach PetJetPro to other end of hose and hand tighten. Enjoy!



For use with automatic compensating valves rated at 0.9 GPM (3.41 L/min) or less.

oxygenics.com

PawSpa®
Powered by oxygenics®

SINK QUICK START GUIDE

FOR MALE THREADED FAUCETS:

STEP 1
Remove smaller end of sink adapter by turning in a counterclockwise direction. Remove faucet aerator and hand tighten larger end of sink adapter in a clockwise direction until firmly attached to the faucet neck.





STEP 2
Attach hose to sink adapter. Attach PetJetPro to hose. Hand tighten only. Enjoy!

FOR FEMALE THREADED FAUCETS:

STEP 1
Remove faucet aerator and hand tighten sink adapter in a clockwise direction until firmly attached to the faucet neck.





STEP 2
Attach hose to sink adapter. Attach PetJetPro to hose. Hand tighten only. Enjoy!

Sink adapter fits two common sizes of faucets after removing aerator:
Female 55/64 in. (22mm) and Male 15/16 in. (24mm).

oxygenics.com

PawSpa®
Powered by oxygenics®

SPIGOT QUICK START GUIDE

STEP 1
In a clockwise direction, hand tighten outdoor spigot adapter to spigot or garden hose until firmly attached.





STEP 2
Attach hose to outdoor spigot adapter.

STEP 3
Attach PetJetPro to hose. Enjoy!



For use with automatic compensating valves rated at 0.9 GPM (3.41 L/min) or less.

oxygenics.com

PawSpa®
Powered by oxygenics®

DUCHA
GUÍA DE INICIO RÁPIDO

PASO 1
Quite su cabezal de ducha existente. Para la extracción, gire el cabezal de ducha existente en el sentido contrario a las agujas del reloj.





PASO 2
Fije el extremo de la manguera al brazo de la ducha y ajuste a mano.

PASO 3
Fije el extremo de la manguera a la lavadora PetJetPro y ajuste a mano. ¡Disfrutar!



Para el uso con válvulas de compensación automáticas nominal de 0.9 GPM (3.41 L/min) o menos.

oxygenics.com

PawSpa®
Powered by oxygenics®

LAVABO
GUÍA DE INICIO RÁPIDO

PARA GRIFOS CON ROSCA MACHO:

PASO 1
Retire el extremo más pequeño del adaptador del fregadero girándolo en sentido antihorario. Retire el aireador del grifo y apriete a mano el extremo más grande del adaptador del fregadero en el sentido de las agujas del reloj hasta que quede firmemente sujeto al cuello del grifo.





PASO 2
Conecte la manguera al adaptador del fregadero. Coloque la lavadora PetJetPro a la manguera. Apriete solo a mano. ¡Disfrutar!

PARA GRIFOS ROSCADOS HEMBRA:

PASO 1
Retire el aireador del grifo y apriete manualmente el adaptador del fregadero en el sentido de las agujas del reloj hasta que quede firmemente sujeto al cuello del grifo.





PASO 2
Conecte la manguera al adaptador del fregadero. Coloque la lavadora PetJetPro a la manguera. Apriete solo a mano. ¡Disfrutar!

El adaptador del fregadero se adapta a dos tamaños comunes de grifos después de quitar el aireador: Hembra de 22mm (55/64 in.) y Macho de 24mm (15/16 in.).

oxygenics.com

PawSpa®
Powered by oxygenics®

ESPIGA
GUÍA DE INICIO RÁPIDO

PASO 1
En el sentido de las agujas del reloj, apriete a mano el adaptador de espiga exterior a la manguera de espiga o jardín hasta que esté firmemente sujeto.





PASO 2
Conecte la manguera al adaptador de espiga exterior.

PASO 3
Conecte la lavadora PetJetPro a la manguera. ¡Disfrutar!



Para el uso con válvulas de compensación automáticas nominal de 0.9 GPM (3.41 L/min) o menos.

oxygenics.com